



Heat-Shrink Tube and Industrial Label Printer

The K-Sun LABELShop_® BEE3+™ is the professional's choice for heat-shrink tube identification and general custom labeling of wires, cables, panels, terminals, face plates, tools and equipment. The BEE3+ offers 11 different heat-shrink tube sizes and colors! **3-Year Unconditional Warranty!**

K-Sun LABELShop® BEE3+™ Kit

Contains the BEE3+ printer with rubber edge guard, AC or DC adapter, case, (1)1/2" black on white tape, (1)1/2" black on white heat-shrink tube cartridge, wrist strap and 6 AA batteries.



Printer Features & Functions

- 5 Heat-Shrink Tube Sizes, 3 Color Combinations
- 3-Year FREE Printer Warranty
- Automatic Tape and Heat-Shrink Tube Cutter
- Keyboard: 67 Key QWERTY-Compatible Keyboard
- Transparent Tape Cover: Instantly Reveals Tape Color, Size and Remaining Tape, Easy to Change
- LCD Display: 12 Characters, 2-Lines Dot Matrix Standard LCD
- LCD Light Adjustment: 5 Dark to Light Settings
- Print Preview: Shows Label Design and Type Style
- Print Technology: High Durability Thermal Transfer
- Print Resolution: 180 DPI
- Print Speed: All Tapes Print 6mm Per Second or 2.36" Per Second
- Print Density: 3 Dark to Light Settings
- Power: Runs on Batteries: 6 AA, AC Power Adapter: 115-240V that Complies with California Energy Reduction Requirements and DC Auto & Truck Adapter: 12V
- Power Management: Automatic Power Off
- Portability: Hand-Held or Desktop Operation. Built-in Frame Handle and Nylon Wrist Strap for Enhanced Portability and Protection.
- Printer Dimensions: 7.4"(wide) x 2.3"(high) x 8.8"(deep)
- Printer Weight: 1.23 Lbs.
- Printer Construction: High Impact Plastic with Rubber Base Guard

Print Functions

- 6 Bar Code Formats: Code 39, Code 128, ITF, UPC-A, UPC-E, CODABAR
- Cable Label Function: "Quick Key" Speeds Design of Wire and Cable Labels
- Horizontal and Vertical Functions
- 14 Fonts, Bitmap Fonts Installed for Print Characters
- Symbols: 1,028 Special Industrial, Medical, Safety, Office, Home and General Symbols, Punctuation, Math, Arrows and More.
- Font Sizes: 6 to 26 Point Depending on Type Style and Tape Width
- Font Functions: Bitmap Smoothing Function
- Font Styles: Bold, Italic, Shadow, Outline, Shadow+Outline
- Lines of Text: 1 to 4 Lines of Text Depending on Tape Width
- Text Alignment: Left, Center, Right
- Tape Feed and Cut Function Key for Manual Advance
- Back Space and Delete Functions
- Frames: 75 Professional and Decorative Print Length: 15", 90 Characters
- Memory Storage: 4 Files
- Euro/Latin Characters: "Quick Key" for Easy Entry of European/Latin Language Characters
- Language Prompts: English/Spanish

Heat-Shrink Tube & Labeling Tape Supplies

- Heat-Shrink Tube Selection: Polyolefin Heat-Shrink Tube Material in 1/8", 3/16", 1/4", 3/8" and 1/2" Widths, 3 Color Combinations
- Tape Selection: 58 Industrial Tapes and 5 Heat-Shrink Tube Materials Two-in-One Tape: Flexible Polyester Base for Wire and Cable Wrap;
- Polyester Provides Durability and Permanent Adhesive Strength for Flat Surfaces Too. Solves Two Requirements with One Tape.
- Tape Width Selection: 5 Widths: 1/6"(4mm), 1/4"(6mm), 3/8"(9mm), 1/2"(12mm), 3/4"(18mm).
- Tape Complies with ANSI/TIA/EIA-606-A Standards.

Environmental and Safety

- Printer Runs on Safe 6.5V DC Power
- Conforms to FCC Class B Standards
- RoHS Directive: Parts Within RoHS Requirements and Standards
- Non-PVC Parts
- Low Battery Warning
- Overheat Detection and Power Shut Off
- Auto Text Storage When Power Out
- Automatic Temperature Sensor
- Battery Reversed Alarm
- Circuit Breaker
- LSAD Adapter: Meets All Requirements for California Energy Commission's Minimum Efficiency and **No-Load Energy Reduction Standards**
- International AC Power Adapters also available

12V-DC Auto & Truck Adapter makes the K-Sun LABELShop[®] BEE3+_™ even more portable and affordable, saving on batteries during field operations!



Meter Australia Pty Ltd Ph 1300 720 481 Fax 1300 720 491 www.meter.com.au sales@meter.com.au

K-Sun LABELShop® *BEE3+*⁷⁷¹ Offers 11 Heat-Shrink Tube Supplies and 58 Industrial Polyester Pressure Sensitive Tape Sizes and Colors

| 1/6" 4mm | BLACK on white #204BW | | | | | | |
|-------------|-----------------------------|----------|-----------|----------|----------|---------|--------|
| 1/4 | BLACK | BLACK | BLACK | WHITE | BLACK | BLACK | BLACK |
| 6mm | on clear | on white | on yellow | on black | on green | on blue | on red |
| | #206BC | #206BW | #206BY | #206WB | #206BG | #206BB | #206BR |
| 3/8" | BLACK | BLACK | BLACK | WHITE | BLACK | BLACK | BLACK |
| 9mm | on clear | on white | on yellow | on black | on green | on blue | on red |
| | #209BC | #209BW | #209BY | #209WB | #209BG | #209BB | #209BR |
| 1 | 5455-555 F | | | | | | |


K-Sun LABELShop® Cartridges come in transparent plastic housings revealing tape color, size and quantity both in and out of printer.



| | 120000 | | 120001 | 1200110 | 120000 | 120000 | #200DH | | | | | | | |
|--------------|--------------------------------------|-------------------------------------|---------------------------------|----------------------------------|---------------------------------|----------------------------------|--|---|--|--|---|---|---------------------------|--|
| 1/2" 12mm | BLACK on clear | BLACK on white | BLACK on yellow | WHITE on black | BLACK on green | BLACK on blue | BLACK on red | GOLD on clear | WHITE on clear | GOLD on black | WHITE on vivid red | WHITE on vivid green | WHITE on vivid blue | Standard & vivid colors, white and clear - 26' (M) |
| | #212BC | #212BW | #212BY | #212WB | #212BG | #212BB | #212BR | #212GC | #212WC | #212GB | #212WR | #212WG | #212WL | tape Length |
| 3/4" 18mm | BLACK on clear | BLACK on translucent matte | BLACK on white | BLUE on white | RED on white | Red on clear | WHITE on clear | WHITE on black | WHITE on vivid red | WHITE on vivid orange | WHITE on vivid green | WHITE on vivid blue | | |
| | #218BC | #218BTM | #218BW | #218BLW | #218RW | #218RC | #218WC | #218WB | #218WR | #218W0 | #218WG | #218WL | | |
| 3/4" 18mm | BLACK on yellow | BLACK on gray | BLACK on blue | BLACK on red | BLACK on orange | BLACK on green | BLACK on violet | BLACK on fluorescent red | BLACK on fluorescent pink Fluorescen | BLACK on fluorescent orange nt colors 16 | BLACK on fluorescent yellow ' (5M) tape | BLACK on fluorescent green length | | |
| | #218BY | #218BX | #218BB | #218BR | #218B0 | #218BG | #218BV | #218FR | #218FP | #218F0 | #218FY | #218FG | | |
| 3/4" 18mm | BLACK on silver holographic | WHITE on rosewood grain | WHITE on granite stone | WHITE on rainbow sunset | BLACK on oakwood grain | BLACK on valence marble | printed are inf to gen repres | n here are d, they cended erally cent actua | | | | | | |
| | #218HLF 5'8" | #218WPR 13'10" | #218SPG 13'10" | #218CGS 13'10" | #218WP0 13'10" | #218SPV 13'10" | tape c | olors. | | | | | | |

Two-in-One Tape

Flexible polyester tape base designed for wire and cable wrapping, tabbing and flagging. Polyester also provides permanent strength for flat surface labeling. No need for different tape materials to do the job! One tape fits all applications.



| Polyolefin Shrink Tube Cartridge Color & Sizes (length=96") | | | | | | | | | |
|--|---------|---------|---------|---------|---------|--|--|--|--|
| Ink on Tube | 1/8" | 3/16" | 1/4" | 3/8" | 1/2" | | | | |
| Black on Red | | 205STBR | | | 211STBR | | | | |
| Black on Yellow | 203STBY | 205STBY | 208STBY | | 211STBY | | | | |
| Black on White | 203STBW | 205STBW | 208STBW | 210STBW | 211STBW | | | | |



K-Sun LABELShop® BEE3+... Offers Labels For Every Application

NE LIN





When You Need A Professional Label, We'll "BEE" There! Meter Australia Pty Ltd Ph 1300 720 481 Fax 1300 720 491 www.meter.com.au sales@meter.com.au

Tape Specifications

- Labeling tapes are made of durable, all-weather polyester base with a permanent, industrial grade acrylic adhesive.
- Tapes are flexible for curved surface labeling.
- Adhesive can adhere to itself for wire tabbing and flagging.
- Tapes have 5-7 year outdoor life.
- Shrink tube material has an industrial grade polyolefin base.
- Shrink rate is 50% or more in diameter and 15% or less in length with shrink ratio of 3 to 1.
- Shrink tube material compliance: UL standard 224, Meets mil-1-23053/5 class 1 and 3, mil-IR 46846 type V ratings.
- Labeling tapes and shrink tube material is printed with resin thermal transfer ribbon for UV, scratch, fade, chemical and smear resistance.

Two-in-one coated tape provides extreme durability for permanent labels.

